


ELECTRONICS PRODUCTS > ELECTRONIC MODULES > ELECTRONIC TERMINAL BLOCKS



MDB 6E Grey

Stock Keeping Unit (SKU): 327099

Cage Clamp Type, 6 pole with light pipe with ground (plastic enclosure)

Commercial Information

Product Sales Code	327099
Package Unit	20 pcs.
Customs Tariff Number	853630300000
Weight Per Unit Including Packaging	0.017 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	6
Color	Grey
Number of Levels	2
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Current	32 A
Nominal Voltage	800 V

CONNECTION DATA

Connection Type	Spring Connection
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	4 mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	12 AWG
Multi-core min. conductor cross-section	0,08 mm²
Multi-core max. conductor cross-section	2,5 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	2,5 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A3
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve	0,5 mm²

DIMENSIONS

Width	6,2 mm
Length	100,5 mm
Height Mr 35X75	63,5 mm
Height MR 35x15	71 mm