


TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > MINI TERMINALS



MYPK 2,5 Grey

Stock Keeping Unit (SKU): 306439

2.5mm² Cage Clamp 2-Pole Mini Panel Terminal Block

Commercial Information

Product Sales Code	306439
Package Unit	100 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.00464 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv
Nominal Current	24 A

Nominal Voltage	800 V
Maximum Load Current	32 A

CONNECTION DATA

Connection Type	Spring Connection
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	4 mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	12 AWG
Multi-core min. conductor cross-section	0,08 mm²
Multi-core max. conductor cross-section	2,5 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	2,5 mm²
Min. Stripping Length	9 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	B3
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve	0,5 mm²

DIMENSIONS

Width	5 mm
Length	33 mm
Height	24,1 mm