



TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > GROUNDING TERMINALS

PRD 16 T

Stock Keeping Unit (SKU): 337750

16 mm² Push-in 2-pole Ground Terminal Block

Commercial Information

| | |
|-----------------------|---------------------|
| Product Sales Code | 337750 |
| Package Unit | 30 pcs. |
| Customs Tariff Number | 853690950000 |

Technical Information

| PRODUCT FEATURES | |
|--|---------------------------|
| Number of Connections | 2 |
| Color | Yellow-gren |
| Number of Levels | 1 |
| Insulation Material | PA |
| UL 94 Flammability Class | VO |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Protective Conductor Type | PE |
| Connection According to Standard | IEC 60947-7-1 |
| Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26 | HL 1 - HL 2 - HL 3 |
| Continuous Operating Temperature max. | 130 °C |
| Continuous Operating Temperature min. | -60 °C |

ELECTRICAL FEATURES

| | |
|-------------------------|-------------|
| Nominal Impulse Voltage | 8 Kv |
| Maximum Load Current | A |

CONNECTION DATA

| | |
|--|---------------------------|
| Connection Type | Push-In |
| Single-core min. conductor cross-section | 0,5 mm² |
| Single-core max. conductor cross-section | 25 mm² |
| Conductor Cross Section Awgkcmil Min | 20 AWG |
| Conductor Cross Section Awgkcmil Max | 4 AWG |
| Multi-core min. conductor cross-section | 0,5 mm² |
| Multi-core max. conductor cross-section | 16 mm² |
| Multi-core min. conductor cross-section with ferrule | 1,5 mm² |
| Multi-core max. conductor cross-section with ferrule | 16 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 4 mm² |
| Min. Stripping Length | 18 mm |
| Max. Stripping Length | 20 mm |
| Internal cylindrical indicator | A7 |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 12 mm |
| Length | 76,80 mm |
| Height Mr 35X75 | 51,40 mm |
| Height MR 35x15 | 58,90 mm |