

TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > MULTILEVEL TERMINALS

PRD 1-FT Blue

Stock Keeping Unit (SKU): 328031*1 mm² Push-in Double-Level 4-pole Phase + Ground Terminal Block*

Commercial Information

Product Sales Code	328031
Package Unit	50 pcs.
Customs Tariff Number	853690950000

Technical Information

PRODUCT FEATURES	
Number of Connections	4
Color	Mavi
Number of Levels	2
Protective Conductor Type	PE
Insulation Material	PA
UL 94 Flammability Class	VO
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL1 - HL2 - HL3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	6 Kv
Nominal Current	13,5 A
Nominal Voltage	500 V
Maximum Load Current	15 A

CONNECTION DATA

Connection Type	Push-in Baglanti
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	1,5 mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	16 AWG
Multi-core min. conductor cross-section	0,14 mm²
Multi-core max. conductor cross-section	1,5 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	1 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A1/B1

DIMENSIONS

Width	3,6 mm
Length	79,80 mm
Height Mr 35X75	50,30 mm
Height MR 35x15	57,80 mm