

ELECTRONICS PRODUCTS &gt; REMOTE I/O &gt; SINGLE-CHANNEL

## EASION-1S-AA111-D

**Stock Keeping Unit (SKU):** 260005*Single-Channel Remote I/O*

### Commercial Information

Product Sales Code	<b>260005</b>
Package Unit	<b>1 pcs.</b>
Customs Tariff Number	<b>853710980019</b>
Weight Per Unit Including Packaging	<b>0.94 kg.</b>

### Technical Information

#### CONNECTION DATA

Connection Type	<b>Screw terminal</b>
-----------------	-----------------------

#### General

Case Width Mm	<b>17,5</b>
Mounting Type	<b>Rail Mounted</b>

#### Power Supply

Voltage	<b>85..265V AC / &lt; 1 W DC</b>
Consumption	<b>&lt; 2,2 VA AC / &lt; 1 W DC</b>

#### Mechanical Properties

Weight G	<b>---</b>
Packaging Quantity	<b>1</b>

#### Environmental Conditions

Operating Temperature	<b>-20 to +60 °C</b>
-----------------------	----------------------

Storage Temperature	<b>-30°C..+80°C</b>
---------------------	---------------------

## Communication

Protocol	<b>Modbus RTU</b>
Baud Rate	<b>1200 -115200 bps adjustable</b>
Parity	
Stop Bit	<b>1</b>
Slave Id	<b>1-247</b>
Isolation	<b>2750V RMS</b>

## Connections

Output Connection	<b>11(COM),14(NO),12(NC)</b>
Input Connections	<b>DI, COM</b>
Power Input	<b>A1,A2</b>

## Relay Output

Number Of Outputs	<b>1 pcs.</b>
Max Switching Current	<b>10 A</b>
Max Switching Power	<b>1250VA</b>
Type	<b>NO (SPST)</b>

## Digital Input

Activation Type	<b>Active Low, Active High</b>
Di Counter	<b>Available</b>
Frequency	
Input Voltage	<b>Kuru Kontak</b>
Number Of Inputs	<b>1 pcs.</b>
Isolation Level	<b>5kVRMS</b>
Min Turn On Time	<b>10msec</b>