



TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > FUSE TERMINALS

AVK 4 FSTLD/NM 48V (Non-polarity) (Grey)

Stock Keeping Unit (SKU): 314139

4mm² Screw 3-level phase + fuse + LED ground terminal block

Commercial Information

| | |
|-------------------------------------|---------------------|
| Product Sales Code | 314139 |
| Package Unit | 30 pcs. |
| Customs Tariff Number | 853690950000 |
| Weight Per Unit Including Packaging | 0.03466 kg. |

Technical Information

| PRODUCT FEATURES | |
|---------------------------------------|--|
| Number of Connections | 5 |
| Color | Gri |
| Number of Levels | 3 |
| Insulation Material | PA |
| UL 94 Flammability Class | V0 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 / IEC 60947-7-2 / IEC 60947-7-3 |
| Continuous Operating Temperature max. | 130 °C |
| Continuous Operating Temperature min. | -60 °C |
| Fuse | G / 5x20 - 5x25 |
| Fuse Type | Cam |

ELECTRICAL FEATURES

| | |
|-------------------------|-----------------------------|
| Nominal Impulse Voltage | 6 Kv |
| Nominal Current | 32 A |
| Nominal Voltage | 48 V (Sigorta) 500 V |

CONNECTION DATA

| | |
|--|---------------------------|
| Connection Type | Vidali Baglanti |
| Single-core min. conductor cross-section | 0,2 mm² |
| Single-core max. conductor cross-section | 6 mm² |
| Conductor Cross Section Awgkcmil Min | 24 AWG |
| Conductor Cross Section Awgkcmil Max | 10 AWG |
| Multi-core min. conductor cross-section | 0,2 mm² |
| Multi-core max. conductor cross-section | 6 mm² |
| Multi-core min. conductor cross-section with ferrule | 0,2 mm² |
| Multi-core max. conductor cross-section with ferrule | 4 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min | 0,5 mm² |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | 2,5 mm² |
| Min. Stripping Length | 8 mm |
| Max. Stripping Length | 9 mm |
| Internal cylindrical indicator | A4 |
| Tightening Torque Min | 0,5 Nm |
| Tightening Torque Max | 0,8 Nm |

DIMENSIONS

| | |
|-----------------|-----------------|
| Width | 8 mm |
| Length | 89,30 mm |
| Height Mr 35X75 | 68,00 mm |
| Height MR 35x15 | 75,45 mm |