



TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > FUSE TERMINALS

AVK 4 FSTLD/NM 110V (Non-polarity) (Grey)

Stock Keeping Unit (SKU): 314149

4mm² Screw 3-level phase + fuse + LED ground terminal block

Commercial Information

Product Sales Code	314149
Package Unit	30 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.03533 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	5
Color	Grey
Number of Levels	3
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1 / IEC 60947-7-2 / IEC 60947-7-3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C
Fuse	G / 5x20 - 5x25
Fuse Type	Glass

ELECTRICAL FEATURES

Nominal Impulse Voltage	6 Kv
Nominal Current	32 A
Nominal Voltage	110 V (Fuse) 500 V

CONNECTION DATA

Connection Type	Screw connection
Single-core min. conductor cross-section	0,2 mm²
Single-core max. conductor cross-section	6 mm²
Conductor Cross Section Awgkcmil Min	24 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,2 mm²
Multi-core max. conductor cross-section	6 mm²
Multi-core min. conductor cross-section with ferrule	0,2 mm²
Multi-core max. conductor cross-section with ferrule	4 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	2,5 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	9 mm
Internal cylindrical indicator	A4
Tightening Torque Min	0,5 Nm
Tightening Torque Max	0,8 Nm

DIMENSIONS

Width	8 mm
Length	89,30 mm
Height Mr 35X75	75,45 mm
Height MR 35x15	68 mm