



TERMINAL BLOCKS > BOLT TYPE TERMINAL BLOCKS > FEED THROUGH TERMINALS

PAK 95-150 Grey

Stock Keeping Unit (SKU): 313089

150mm² Bolt-Type Feed-Through Terminal Block

Commercial Information

Product Sales Code	313089
Package Unit	5 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.272 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Bil.Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	3
Insulation Material Group	1
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv Kv
Nominal Current	309 A
Nominal Voltage	1000 V

CONNECTION DATA

Connection Type	Bolt Connection
Tightening Torque Min	10 Nm
Tightening Torque Max	20 Nm
Hole Diameter Min	10,5 mm
Din 46234 Cable Lug Min	6 mm²
Din 46234 Cable Lug Max	150 mm²
Din 46235 Cable Lug Min	16 mm²
Din 46235 Cable Lug Max	150 mm²
Din 46234 Cable Lug Min	10 AWG
Din 46234 Cable Lug Max	300 kcmil
Din 46235 Cable Lug Min	6 AWG
Din 46235 Cable Lug Max	300 kcmil

DIMENSIONS

Width	41,00 mm
Length	144 mm
Height Mr 35X75	74 mm
Height MR 35x15	81,5 mm