

TERMINAL BLOCKS > OTHER PRODUCTS > PANEL SOCKET

PAP LT Grey

Stock Keeping Unit (SKU): 670200*Panel Socket (Earth - Led)*

Commercial Information

Product Sales Code	670200
Package Unit	6 pcs.
Customs Tariff Number	853669900018
Weight Per Unit Including Packaging	0.07 kg.

Technical Information

PRODUCT FEATURES

Color	Bil.Grey
Insulation Material	PC
UL 94 Flammability Class	V2
Continuous Operating Temperature max.	60 °C
Continuous Operating Temperature min.	-20 °C

ELECTRICAL FEATURES

Nominal Current	16 A
Nominal Voltage	250 V

CONNECTION DATA

Connection Type	Screw Connection
Single-core min. conductor cross-section	0,5 mm²
Single-core max. conductor cross-section	10 mm²
Conductor Cross Section Awgkcmil Min	20 AWG

Conductor Cross Section Awgkcmil Max	4 AWG
Multi-core min. conductor cross-section	0,5 mm²
Multi-core max. conductor cross-section	10 mm²
Multi-core min. conductor cross-section with ferrule	0,5 mm²
Multi-core max. conductor cross-section with ferrule	6 mm²
Min. Stripping Length	10 mm
Tightening Torque Min	0,8 Nm
Tightening Torque Max	1,2 Nm

DIMENSIONS

Width	42 mm
Length	74,80 mm
Height Mr 35X75	49 mm
Height MR 35x15	56,50 mm