

TERMINAL BLOCKS > OTHER PRODUCTS > PANEL SOCKET



## PAP U Grey

**Stock Keeping Unit (SKU):** 670300

*UPS Panel socket*

### Commercial Information

|                                     |                     |
|-------------------------------------|---------------------|
| Product Sales Code                  | <b>670300</b>       |
| Package Unit                        | <b>6 pcs.</b>       |
| Customs Tariff Number               | <b>853669900018</b> |
| Weight Per Unit Including Packaging | <b>0.07 kg.</b>     |

### Technical Information

#### PRODUCT FEATURES

|                                       |                 |
|---------------------------------------|-----------------|
| Color                                 | <b>Bil.Grey</b> |
| Insulation Material                   | <b>PC</b>       |
| UL 94 Flammability Class              | <b>V2</b>       |
| Continuous Operating Temperature max. | <b>60 °C</b>    |
| Continuous Operating Temperature min. | <b>-20 °C</b>   |

#### ELECTRICAL FEATURES

|                 |              |
|-----------------|--------------|
| Nominal Current | <b>16 A</b>  |
| Nominal Voltage | <b>250 V</b> |

#### CONNECTION DATA

|  |                           |
|--|---------------------------|
| Connection Type                          | <b>Screw Connection</b>   |
| Single-core min. conductor cross-section | <b>0,5 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section | <b>10 mm<sup>2</sup></b>  |

|  |                           |
|--|---------------------------|
| Conductor Cross Section Awgkcmil Min                 | <b>20 AWG</b>             |
| Conductor Cross Section Awgkcmil Max                 | <b>4 AWG</b>              |
| Multi-core min. conductor cross-section              | <b>0,5 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section              | <b>10 mm<sup>2</sup></b>  |
| Multi-core min. conductor cross-section with ferrule | <b>0,5 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section with ferrule | <b>6 mm<sup>2</sup></b>   |
| Min. Stripping Length                                | <b>10 mm</b>              |
| Tightening Torque Min                                | <b>0,8 Nm</b>             |
| Tightening Torque Max                                | <b>1,2 Nm</b>             |

## DIMENSIONS

|                 |                 |
|-----------------|-----------------|
| Width           | <b>42 mm</b>    |
| Length          | <b>74,80 mm</b> |
| Height Mr 35X75 | <b>49 mm</b>    |
| Height MR 35x15 | <b>56,50 mm</b> |