


TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > MULTILEVEL TERMINALS



PIK 10N Grey

Stock Keeping Unit (SKU): 319909

Screw Type, 10 mm² 2 layer feed-through terminal block

Commercial Information

Product Sales Code	319909
Package Unit	20 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.041 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	4
Color	Grey
Number of Levels	2
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv
Nominal Current	57 A

Nominal Voltage	800 V
Maximum Load Current	76 A

CONNECTION DATA

Connection Type	Screw Connection
Single-core min. conductor cross-section	1,5 mm²
Single-core max. conductor cross-section	16 mm²
Conductor Cross Section Awgkcmil Min	16 AWG
Conductor Cross Section Awgkcmil Max	6 AWG
Multi-core min. conductor cross-section	1,5 mm²
Multi-core max. conductor cross-section	16 mm²
Multi-core min. conductor cross-section with ferrule	1,5 mm²
Multi-core max. conductor cross-section with ferrule	16 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	6 mm²
Min. Stripping Length	10 mm
Max. Stripping Length	12 mm
Internal cylindrical indicator	B6
Tightening Torque Min	1,2 Nm
Tightening Torque Max	1,8 Nm

DIMENSIONS

Width	10 mm
Length	78,65 mm
Height Mr 35X75	72,90 mm
Height MR 35x15	80,40 mm