



TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > FEED THROUGH TERMINALS

PRD 10 Grey

Stock Keeping Unit (SKU): 329659

Push-in Type, with orange button, 10 mm² feed through terminal block

Commercial Information

| | |
|-------------------------------------|---------------------|
| Product Sales Code | 329659 |
| Package Unit | 40 pcs. |
| Customs Tariff Number | 853690950000 |
| Weight Per Unit Including Packaging | 0.026 kg. |

Technical Information

| PRODUCT FEATURES | |
|---------------------------------------|----------------------|
| Number of Connections | 2 |
| Color | Grey |
| Number of Levels | 1 |
| Insulation Material | PA |
| UL 94 Flammability Class | V0 |
| Impulse Voltage Category | III |
| Insulation Material Group | I |
| Pollution Degree | 3 |
| Connection According to Standard | IEC 60947-7-1 |
| Continuous Operating Temperature max. | 130 °C |
| Continuous Operating Temperature min. | -60 °C |
| ELECTRICAL FEATURES | |
| Nominal Impulse Voltage | 8 Kv |

| | |
|----------------------|---------------|
| Nominal Current | 57 A |
| Nominal Voltage | 1000 V |
| Maximum Load Current | 65 A |

CONNECTION DATA

| | |
|--|---------------------------|
| Connection Type | Push-In Connection |
| Single-core min. conductor cross-section | 0,2 mm² |
| Single-core max. conductor cross-section | 16 mm² |
| Conductor Cross Section Awgkcmil Min | 24 AWG |
| Conductor Cross Section Awgkcmil Max | 6 AWG |
| Multi-core min. conductor cross-section | 0,2 mm² |
| Multi-core max. conductor cross-section | 10 mm² |
| Min. Stripping Length | 16 mm |
| Max. Stripping Length | 18 mm |
| Internal cylindrical indicator | A6 |

DIMENSIONS

| | |
|-----------------|----------------|
| Width | 10 mm |
| Length | 71 mm |
| Height Mr 35X75 | 49,7 mm |
| Height MR 35x15 | 57,2 mm |