



TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > GROUNDING TERMINALS

## PRD 1CT Sari/Yesil

Stock Keeping Unit (SKU): 337600

1 mm<sup>2</sup> push-in bağlantılı, 4 kutuplu, toprak klemensi

### Commercial Information

|                       |                     |
|-----------------------|---------------------|
| Product Sales Code    | <b>337600</b>       |
| Package Unit          | <b>50 Ad.</b>       |
| Customs Tariff Number | <b>853690950000</b> |

### Technical Information

| PRODUCT FEATURES   |                        |
|--|------------------------|
| Number of Connections  | <b>4</b>               |
| Color  | <b>Sari/Yesil</b>      |
| Number of Levels   | <b>1</b>               |
| Insulation Material  | <b>PA</b>              |
| UL 94 Flammability Class   | <b>VO</b>              |
| Impulse Voltage Category   | <b>III</b>             |
| Insulation Material Group  | <b>I</b>               |
| Pollution Degree   | <b>3</b>               |
| Koruma Iletken Tipi  | <b>PE</b>              |
| Connection According to Standard                                   | <b>IEC 60947-7-1</b>   |
| Demiryolu Araclarında Yangin Koruma Din En 45545 2 R22 R23 R24 R26 | <b>HL1 - HL2 - HL3</b> |
| Continuous Operating Temperature max.                              | <b>130 °C</b>          |
| Continuous Operating Temperature min.                              | <b>-60 °C</b>          |

### ELECTRICAL FEATURES

|                         |             |
|-------------------------|-------------|
| Nominal Impulse Voltage | <b>8 Kv</b> |
|-------------------------|-------------|

## CONNECTION DATA

|  |                            |
|--|----------------------------|
| Connection Type  | <b>Push-in Baglanti</b>    |
| Single-core min. conductor cross-section                   | <b>0,08 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section                   | <b>1,5 mm<sup>2</sup></b>  |
| Iletken Kesit Alani Awgcmil Min                            | <b>28 AWG</b>              |
| Iletken Kesit Alani Awgcmil Max                            | <b>16 AWG</b>              |
| Multi-core min. conductor cross-section                    | <b>0,14 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section                    | <b>1,5 mm<sup>2</sup></b>  |
| Multi-core min. conductor cross-section with ferrule       | <b>0,14 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section with ferrule       | <b>1 mm<sup>2</sup></b>    |
| Min. Stripping Length                                      | <b>8 mm</b>                |
| Max. Stripping Length                                      | <b>10 mm</b>               |
| Internal cylindrical indicator                             | <b>A1/B1</b>               |
| Cok Damarli Maks Iletken Kesit Alani Izolasyonsuz Yuksuklu | <b>1,5 mm<sup>2</sup></b>  |

## DIMENSIONS

|                   |                 |
|-------------------|-----------------|
| Width             | <b>3,6 mm</b>   |
| Length            | <b>78,10 mm</b> |
| Yukseklk Mr 35X75 | <b>37,30 mm</b> |
| Height MR 35x15   | <b>44,80 mm</b> |