



TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > MULTI-CONDUCTOR
TERMINAL BLOCKS

PRD 1E Gri

Stock Keeping Unit (SKU): 328019

1 mm² push-in bağlantılı 3 kutuplu geçiş klemensi

Commercial Information

Product Sales Code	328019
Package Unit	50 ad.
Customs Tariff Number	853690950000

Technical Information

PRODUCT FEATURES	
Number of Connections	3
Color	Gri
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv
Nominal Current	13,5 A

Nominal Voltage	800 V
Maximum Load Current	17,5 A

CONNECTION DATA

Connection Type	Push-In Baglanti
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	1,5 mm²
Iletken Kesit Alani Awgkcmil Min	28 AWG
Iletken Kesit Alani Awgkcmil Max	16 AWG
Multi-core min. conductor cross-section	0,14 mm²
Multi-core max. conductor cross-section	1,5 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	1 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A1/B1
Cok Damarli Maks Iletken Kesit Alani Izolasyonsuz Yuksuklu	1,5 mm²

DIMENSIONS

Width	3,6 mm
Length	65,20 mm
Yukseklk Mr 35X75	37,30 mm
Height MR 35x15	44,80 mm