

TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > ELECTRONICS
COMPONENT TERMINALS

PRD 4ED-B Gri

Stock Keeping Unit (SKU): 329059*4 mm² push-in bağlantılı 3 kutuplu diyotlu klemens*

Commercial Information

Product Sales Code	329059
Package Unit	50 Ad.
Customs Tariff Number	853690950000

Technical Information

PRODUCT FEATURES	
Number of Connections	3
Color	Gri
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Demiryolu Araclarında Yangın Koruma Din En 45545 2 R22 R23 R24 R26	HL1 - HL2 - HL3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C
Not	Maks. akım diyot tarafından belirlenir. 1N 4007 diyotu, ters gerilim

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Current	1 A
Nominal Voltage	800 V

CONNECTION DATA

Connection Type	Push-In Bağlantı
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	6 mm²
İletken Kesit Alani Awgcmil Min	28 AWG
İletken Kesit Alani Awgcmil Max	10 AWG
Multi-core min. conductor cross-section	0,14 mm²
Multi-core max. conductor cross-section	4 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	4 mm²
2 conductors of the same cross-section, multi-core, twin ferrule with plastic sleeve, min.	1 mm²
2 conductors of the same cross-section, multi-core, twin ferrule with plastic sleeve, max.	mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A4

DIMENSIONS

Width	6,2 mm
Length	76,6 mm
Yukseklık Mr 35X75	38,30 mm
Height MR 35x15	45,80 mm