


TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > GROUNDING TERMINALS



PRD 6ET Yellow/Green

Stock Keeping Unit (SKU): 337720

Push-in Type, with orange button, 6 mm² 1 input-2 output grounding terminal block

Commercial Information

Product Sales Code	337720
Package Unit	50 pcs.
Customs Tariff Number	853690950000

Technical Information

PRODUCT FEATURES	
Number of Connections	3
Color	Yellow/Green
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL1 - HL2 - HL3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Push-In Connection
Single-core min. conductor cross-section	0,2 mm²
Single-core max. conductor cross-section	10 mm²
Conductor Cross Section Awgkcmil Min	24 AWG
Conductor Cross Section Awgkcmil Max	8 AWG
Multi-core min. conductor cross-section	0,2 mm²
Multi-core max. conductor cross-section	6 mm²
Multi-core min. conductor cross-section with ferrule	0,25 mm²
Multi-core max. conductor cross-section with ferrule	6 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	1,5 mm²
Min. Stripping Length	10 mm
Max. Stripping Length	12 mm
Internal cylindrical indicator	A5

DIMENSIONS

Width	8 mm
Length	88,6 mm
Height Mr 35X75	39,45 mm
Height MR 35x15	46,95 mm