



TERMINAL BLOCKS > OTHER PRODUCTS > TERMINAL BLOCKS

## PSK 1/12 Beige

**Stock Keeping Unit (SKU):** 420120

*Screw Type, 2,5 mm<sup>2</sup> 22 pole terminal strip*

### Commercial Information

Product Sales Code	<b>420120</b>
Package Unit	<b>75 pcs.</b>
Customs Tariff Number	<b>853690950000</b>
Weight Per Unit Including Packaging	<b>0.04 kg.</b>

### Technical Information

PRODUCT FEATURES	
Number of Connections	<b>24</b>
Color	<b>Beige</b>
Number of Levels	<b>12</b>
Insulation Material	<b>PA</b>
UL 94 Flammability Class	<b>V2</b>
Impulse Voltage Category	<b>III</b>
Insulation Material Group	<b>I</b>
Pollution Degree	<b>3</b>
Connection According to Standard	<b>IEC 60998-2-1</b>
Continuous Operating Temperature max.	<b>120 °C</b>
Continuous Operating Temperature min.	<b>-55 °C</b>

ELECTRICAL FEATURES	
Nominal Impulse Voltage	<b>3 Kv</b>

Nominal Current	<b>24 A</b>
Nominal Voltage	<b>400 V</b>

## CONNECTION DATA

Connection Type	<b>Screw Connection</b>
Single-core min. conductor cross-section	<b>0,2 mm<sup>2</sup></b>
Single-core max. conductor cross-section	<b>4 mm<sup>2</sup></b>
Conductor Cross Section Awgkcmil Min	<b>24 AWG</b>
Conductor Cross Section Awgkcmil Max	<b>12 AWG</b>
Multi-core min. conductor cross-section	<b>0,2 mm<sup>2</sup></b>
Multi-core max. conductor cross-section	<b>4 mm<sup>2</sup></b>
Multi-core min. conductor cross-section with ferrule	<b>0,25 mm<sup>2</sup></b>
Multi-core max. conductor cross-section with ferrule	<b>2,5 mm<sup>2</sup></b>
Min. Stripping Length	<b>5 mm</b>
Max. Stripping Length	<b>6 mm</b>
Internal cylindrical indicator	<b>A3</b>
Tightening Torque Min	<b>0,4 Nm</b>
Tightening Torque Max	<b>0,6 Nm</b>

## DIMENSIONS

Width	<b>15 mm</b>
Length	<b>109 mm</b>
Height	<b>16,25 mm</b>