

TERMINAL BLOCKS > OTHER PRODUCTS > TERMINAL BLOCKS

PSK 2/10 Beige

Stock Keeping Unit (SKU): 421100

Screw Type, 4 mm² 20 pole terminal strip

Commercial Information

Product Sales Code	**421100**
Package Unit	**20 pcs.**
Customs Tariff Number	**853690950000**
Weight Per Unit Including Packaging	**0.08875 kg.**

Technical Information

PRODUCT SPECIFICATIONS	
Number of Connections	**20**
Color	**Beige**
Number of Levels	**10**
Insulation Material	**PA**
UL 94 Flammability Class	**V2**
Impulse Voltage Category	**III**
Insulation Material Group	**I**
Pollution Degree	**3**
Connection According to Standard	**IEC 60998-2-1**
Continuous Operating Temperature Max.	**120 °C**
Continuous Operating Temperature Min.	**-55 °C**

ELECTRICAL SPECIFICATIONS	
Nominal Impulse Voltage	**6 Kv**
Nominal Current	**41 A**

Nominal Voltage	**600 V**

CONNECTION DATA

Connection Type	**Screw Connection**
Min. Solid Conductor Cross-Sectional Area	**0,2 mm²**
Max. Solid Conductor Cross-Sectional Area	**10 mm²**
Conductor Cross-Section AWG/kcmil Min.	**24 AWG**
Conductor Cross-Section AWG/kcmil Max.	**8 AWG**
Min. Stranded Conductor Cross-Sectional Area	**0,2 mm²**
Max. Stranded Conductor Cross-Sectional Area	**10 mm²**
Min. Stranded Conductor Cross-Sectional Area with Ferrule	**0,25 mm²**
Max. Stranded Conductor Cross-Sectional Area with Ferrule	**6 mm²**
Min. Stripping Length	**8 mm**
Max. Stripping Length	**9 mm**
Internal Cylindrical Indicator	**B5**
Tightening Torque Min.	**0,5 Nm**
Tightening Torque Max.	**0,8 Nm**

DIMENSIONS

Width	**22,70 mm**
Length	**125,20 mm**
Height	**21,60 mm**

Certificates

CE

UKCA

TSE

ROHS

Accessories

SCREWDRIVERS



Product Code: 561240

IKT-D 4 (0,8 x Ø4,0)