



TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > FEED THROUGH TERMINALS

## PYK 1,5M

**Stock Keeping Unit (SKU):** 307019

*Push-in Type, 1,5 mm<sup>2</sup> feed-through mini terminal block (gray)*

### Commercial Information

|                                     |                     |
|-------------------------------------|---------------------|
| Product Sales Code                  | <b>307019</b>       |
| Package Unit                        | <b>100 pcs.</b>     |
| Customs Tariff Number               | <b>853690950000</b> |
| Weight Per Unit Including Packaging | <b>0.0046 kg.</b>   |

### Technical Information

| PRODUCT FEATURES                      |                      |
|---------------------------------------|----------------------|
| Number of Connections                 | <b>2</b>             |
| Color                                 | <b>Grey</b>          |
| Number of Levels                      | <b>1</b>             |
| Insulation Material                   | <b>PA</b>            |
| UL 94 Flammability Class              | <b>V2</b>            |
| Impulse Voltage Category              | <b>III</b>           |
| Insulation Material Group             | <b>I</b>             |
| Pollution Degree                      | <b>3</b>             |
| Connection According to Standard      | <b>IEC 60947-7-1</b> |
| Continuous Operating Temperature max. | <b>120 °C</b>        |
| Continuous Operating Temperature min. | <b>-55 °C</b>        |

| ELECTRICAL FEATURES     |             |
|-------------------------|-------------|
| Nominal Impulse Voltage | <b>8 Kv</b> |

|                      |               |
|----------------------|---------------|
| Nominal Current      | <b>17,5 A</b> |
| Nominal Voltage      | <b>800 V</b>  |
| Maximum Load Current | <b>24 A</b>   |

## CONNECTION DATA

|  |                            |
|--|----------------------------|
| Connection Type  | <b>Push-In Connection</b>  |
| Single-core min. conductor cross-section   | <b>0,34 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section   | <b>2,5 mm<sup>2</sup></b>  |
| Conductor Cross Section Awgkcmil Min   | <b>22 AWG</b>              |
| Conductor Cross Section Awgkcmil Max   | <b>14 AWG</b>              |
| Multi-core min. conductor cross-section  | <b>0,34 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section  | <b>1,5 mm<sup>2</sup></b>  |
| Multi-core min. conductor cross-section with ferrule                                   | <b>0,5 mm<sup>2</sup></b>  |
| Multi-core max. conductor cross-section with ferrule                                   | <b>1,5 mm<sup>2</sup></b>  |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max | <b>0,5 mm<sup>2</sup></b>  |
| Min. Stripping Length  | <b>9 mm</b>                |
| Max. Stripping Length  | <b>10 mm</b>               |
| Internal cylindrical indicator   | <b>A1-B1</b>               |

## DIMENSIONS

|                 |                |
|-----------------|----------------|
| Width           | <b>4,2 mm</b>  |
| Length          | <b>52 mm</b>   |
| Height Mr 35X75 | <b>37,8 mm</b> |
| Height Mr 15X55 | <b>45,3 mm</b> |