



TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > ELECTRONICS
COMPONENT TERMINALS

PYK 1,5MCD_A

Stock Keeping Unit (SKU): 307049

Push-in Type, 1,5 mm² 2 pole component mini terminal block (gray)

Commercial Information

Product Sales Code	307049
Package Unit	70 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.006857 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	4
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C
Note	Max. current is determined by the diode. 1N 4007 diode, reverse voltage

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Current	0,5 A
Nominal Voltage	800 V
Maximum Load Current	0,5 A

CONNECTION DATA

Connection Type	Push-In Connection
Single-core min. conductor cross-section	0,34 mm²
Single-core max. conductor cross-section	2,5 mm²
Conductor Cross Section Awgkcmil Min	22 AWG
Conductor Cross Section Awgkcmil Max	14 AWG
Multi-core min. conductor cross-section	0,34 mm²
Multi-core max. conductor cross-section	1,5 mm²
Multi-core min. conductor cross-section with ferrule	0,5 mm²
Multi-core max. conductor cross-section with ferrule	1,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	0,5 mm²
Min. Stripping Length	9 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A1-B1

DIMENSIONS

Width	4,2 mm
Length	75,10 mm
Height Mr 35X75	37,8 mm
Height Mr 15X55	45,3 mm