


TERMINAL BLOCKS > PUSH-IN TYPE TERMINAL BLOCKS > DISCONNECT TERMINALS



PYK 2,5A Grey

Stock Keeping Unit (SKU): 307169

Push-in Type, 2,5 mm² knife disconnect terminal block (gray)

Commercial Information

Product Sales Code	307169
Package Unit	50 pcs.
Customs Tariff Number	853630300000
Weight Per Unit Including Packaging	0.0092 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Continuous Operating Temperature max.	120 °C
Continuous Operating Temperature min.	-55 °C

ELECTRICAL FEATURES	
Nominal Impulse Voltage	8 Kv

Nominal Current	20 A
Nominal Voltage	400 V
Maximum Load Current	20 A

CONNECTION DATA

Connection Type	Push-In Connection
Single-core min. conductor cross-section	0,34 mm²
Single-core max. conductor cross-section	4 mm²
Conductor Cross Section Awgkcmil Min	22 AWG
Conductor Cross Section Awgkcmil Max	12 AWG
Multi-core min. conductor cross-section	0,34 mm²
Multi-core max. conductor cross-section	2,5 mm²
Multi-core min. conductor cross-section with ferrule	0,25 mm²
Multi-core max. conductor cross-section with ferrule	2,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
Min. Stripping Length	9 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A3

DIMENSIONS

Width	5 mm
Length	70,8 mm
Height Mr 35X75	43,7 mm
Height MR 35x15	51,2 mm