

TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > DISCONNECT TERMINALS

SRD 2,5CA

Stock Keeping Unit (SKU): 311319

Cage Clamp Type, 2,5 mm² 2 input-2 output disconnect terminal block

Commercial Information

Product Sales Code	**311319**
Package Unit	**50 pcs.**
Customs Tariff Number	**853690950000**
Weight Per Unit Including Packaging	**0.01788 kg.**

Technical Information

PRODUCT FEATURES	
Number of Connections	**4**
Color	**Grey**
Number of Levels	**1**
Insulation Material	**PA**
UL 94 Flammability Class	**V0**
Impulse Voltage Category	**III**
Insulation Material Group	**I**
Pollution Degree	**3**
Connection According to Standard	**IEC 60947-7-1**
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	**HL1 - HL2 - HL3**
Continuous Operating Temperature max.	**130 °C**
Continuous Operating Temperature min.	**-60 °C**

ELECTRICAL FEATURES

Nominal Impulse Voltage	**6 Kv**
Nominal Current	**20 A**
Nominal Voltage	**500 V**

CONNECTION DATA

Connection Type	**Spring Connection**
Single-core min. conductor cross-section	**0,08 mm²**
Single-core max. conductor cross-section	**4 mm²**
Conductor Cross Section Awgkcmil Min	**28 AWG**
Conductor Cross Section Awgkcmil Max	**12 AWG**
Multi-core min. conductor cross-section	**0,14 mm²**
Multi-core max. conductor cross-section	**2,5 mm²**
Multi-core min. conductor cross-section with ferrule	**0,14 mm²**
Multi-core max. conductor cross-section with ferrule	**2,5 mm²**
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	**0,5 mm²**
Min. Stripping Length	**8 mm**
Max. Stripping Length	**10 mm**
Internal cylindrical indicator	**A3**

DIMENSIONS

Width	**5,2 mm**
Length	**91,30 mm**
Height Mr 35X75	**38,90 mm**
Height MR 35x15	**46,40 mm**