


TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > DISCONNECT
TERMINALS



SRD 2,5CA

Stock Keeping Unit (SKU): 311319

Cage Clamp Type, 2,5 mm² 2 input-2 output disconnect terminal
block

Commercial Information

Product Sales Code	311319
Package Unit	50 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.01788 kg.

Technical Information

PRODUCT SPECIFICATIONS	
Number of Connections	4
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection in Railway Vehicles (DIN EN 45545-2 R22/R23/R24/R26)	HL1 - HL2 - HL3
Continuous Operating Temperature Max.	130 °C
Continuous Operating Temperature Min.	-60 °C

ELECTRICAL SPECIFICATIONS

Nominal Impulse Voltage	6 Kv
Nominal Current	20 A
Nominal Voltage	500 V

CONNECTION DATA

Connection Type	Spring Connection
Min. Solid Conductor Cross-Sectional Area	0,08 mm²
Max. Solid Conductor Cross-Sectional Area	4 mm²
Conductor Cross-Section AWG/kcmil Min.	28 AWG
Conductor Cross-Section AWG/kcmil Max.	12 AWG
Min. Stranded Conductor Cross-Sectional Area	0,14 mm²
Max. Stranded Conductor Cross-Sectional Area	2,5 mm²
Min. Stranded Conductor Cross-Sectional Area with Ferrule	0,14 mm²
Max. Stranded Conductor Cross-Sectional Area with Ferrule	2,5 mm²
Max. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	0,5 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal Cylindrical Indicator	A3

DIMENSIONS

Width	5,2 mm
Length	91,30 mm
Height MR 35x7.5	38,90 mm
Height MR 35x15	46,40 mm

Certificates



cULus



ATEX



CE



ROHS



UKCA

**cULus**

Conductor Cross-section	AWG 28-12
Nominal Current	20 A
Nominal Voltage	300 V

**ATEX**

Nominal Current	20 A
Nominal Voltage	350 V

Accessories

ZINC COATED



Product Code: 500601

MR 35x7.5 Straight (1m) Zinc Coated Rail

Product Code: 500604

MR 35x7.5 Slotted DIN Rail (2 m), Galvanized

Product Code: 500609

MR 35x15 Slotted (2m) Zinc Coated Rail

Product Code: 500602

MR 35x7.5 Slotted (1m) Zinc Coated Rail

Product Code: 500603

MR 35x7.5 Straight (2m) Zinc Coated Rail

Product Code: 500606

MR 35x15 Straight (1m) Zinc Coated Rail

Product Code: 500608

MR 35x15 Straight (2m) Zinc Coated Rail

ÇINKO KAPLI



Product Code: 500607

MR 35x15 Slotlu (1m) Çinko Kaplı Ray

GALVANIZED



Product Code: 500602E

MR 35x7.5 Slotted (1m) Rail (Galvanized)

Product Code: 500603E

MR 35x7,5 Plain (2m) Rail (Galvanized)



Product Code: 500604E

MR 35x7,5 SLOTT (2m) RAIL (GALVANIZED)



Product Code: 500609E

MR 35x15 Slotted (2m) Rail (Galvanized)

TEST SOCKETS



Product Code: 493020

TF (Ø 2)

TERMINAL THERMAL PRINTER LABELS



Product Code: 810450

D-NS 5,2x6

END PLATE/COVER

Product Code: 451169

NPP/SRD 2,5CA Grey

SEPARATION PLATE

Product Code: 464089

APP/SRD 2,5CA Grey

PLUG-IN CROSS CONNECTOR



Product Code: 470102

CS 2,5/2



Product Code: 470103

CS 2,5/3



Product Code: 470104

CS 2,5/4



Product Code: 470105

CS 2,5/5



Product Code: 470109

CS 2,5/10



Product Code: 470170

CS 2,5/20

END STOP



Product Code: 497009

KD 3/NM Grey

Product Code: 497019

KD 4/NM Grey

Product Code: 497059

KD 7/NM Grey

Product Code: 497069

KD 8/NM Grey

TERMINAL STRIP LABELS



Product Code: 1020100

SLF-P1 W 11,2mm x 15m
