


TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > DISCONNECT
TERMINALS



SRD 2,5CA

Stock Keeping Unit (SKU): 311319

Cage Clamp Type, 2,5 mm² 2 input-2 output disconnect terminal
block

Commercial Information

Product Sales Code	311319
Package Unit	50 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.01788 kg.

Technical Information

PRODUCT SPECIFICATIONS	
Number of Connections	4
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection in Railway Vehicles (DIN EN 45545-2 R22/R23/R24/R26)	HL1 - HL2 - HL3
Continuous Operating Temperature Max.	130 °C
Continuous Operating Temperature Min.	-60 °C

ELECTRICAL SPECIFICATIONS

Nominal Impulse Voltage	6 Kv
Nominal Current	20 A
Nominal Voltage	500 V

CONNECTION DATA

Connection Type	Spring Connection
Min. Solid Conductor Cross-Sectional Area	0,08 mm²
Max. Solid Conductor Cross-Sectional Area	4 mm²
Conductor Cross-Section AWG/kcmil Min.	28 AWG
Conductor Cross-Section AWG/kcmil Max.	12 AWG
Min. Stranded Conductor Cross-Sectional Area	0,14 mm²
Max. Stranded Conductor Cross-Sectional Area	2,5 mm²
Min. Stranded Conductor Cross-Sectional Area with Ferrule	0,14 mm²
Max. Stranded Conductor Cross-Sectional Area with Ferrule	2,5 mm²
Max. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	0,5 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal Cylindrical Indicator	A3

DIMENSIONS

Width	5,2 mm
Length	91,30 mm
Height MR 35x7.5	38,90 mm
Height MR 35x15	46,40 mm