



TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > ELECTRONICS
COMPONENT TERMINALS

SRD 4 D_A/Grey

Stock Keeping Unit (SKU): 311689

Cage Clamp Type, 4 mm² component terminal block (diode)

Commercial Information

Product Sales Code	311689
Package Unit	50 pcs.
Customs Tariff Number	853630100000
Weight Per Unit Including Packaging	0.009 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Voltage	800 V
Nominal Current In Fuse	1 A

CONNECTION DATA

Connection Type	Yayli baglanti / Spring connection
Single-core min. conductor cross-section	0,08 mm² mm²
Single-core max. conductor cross-section	6 mm² mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,14 mm² mm²
Multi-core max. conductor cross-section	4 mm² mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm² mm²
Multi-core max. conductor cross-section with ferrule	4 mm² mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	1 mm² mm²
Min. Stripping Length	8 mm mm
Max. Stripping Length	10 mm mm
Internal cylindrical indicator	A4

DIMENSIONS

Width	6,2 mm
Length	60,10 mm
Height Mr 35X75	38,3 mm
Height MR 35x15	45,80 mm