

TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > DISCONNECT
TERMINALS

SRD 4A Blue

Stock Keeping Unit (SKU): 311861*4 mm² Cage Clamp Disconnect Terminal Block*

Commercial Information

Product Sales Code	311861
Package Unit	50 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.0128 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Blue
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	6 Kv
Nominal Current	20 A
Nominal Voltage	500 V
Maximum Load Current	20 A

CONNECTION DATA

Connection Type	Spring Connection
Single-core min. conductor cross-section	0,08 mm² mm²
Single-core max. conductor cross-section	6 mm² mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,14 mm² mm²
Multi-core max. conductor cross-section	4 mm² mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm² mm²
Multi-core max. conductor cross-section with ferrule	4 mm² mm²
Min. Stripping Length	8 mm mm
Max. Stripping Length	10 mm mm
Internal cylindrical indicator	A4
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve	1 mm²

DIMENSIONS

Width	6,2 mm
Length	76,60 mm
Height Mr 35X75	38,3 mm
Height MR 35x15	45,80 mm