

TERMINAL BLOCKS &gt; SPRING CLAMP TYPE TERMINAL BLOCKS &gt; FUSE TERMINALS

## SRD 4S Beige

**Stock Keeping Unit (SKU):** 312110*4 mm<sup>2</sup> Cage Clamp Fuse Terminal Block (5×20)*

### Commercial Information

|                                     |                     |
|-------------------------------------|---------------------|
| Product Sales Code                  | <b>312110</b>       |
| Package Unit                        | <b>30 pcs.</b>      |
| Customs Tariff Number               | <b>853690950000</b> |
| Weight Per Unit Including Packaging | <b>0.018 kg.</b>    |

### Technical Information

| PRODUCT FEATURES   |                       |
|--|-----------------------|
| Number of Connections  | <b>2</b>              |
| Color  | <b>Beige</b>          |
| Number of Levels   | <b>1</b>              |
| Insulation Material  | <b>PA</b>             |
| UL 94 Flammability Class   | <b>V0</b>             |
| Impulse Voltage Category   | <b>III</b>            |
| Insulation Material Group  | <b>I</b>              |
| Pollution Degree   | <b>3</b>              |
| Connection According to Standard                                   | <b>IEC 60947-7-3</b>  |
| Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26 | <b>HL 1-HL 2-HL 3</b> |
| Continuous Operating Temperature max.                              | <b>130 °C</b>         |
| Continuous Operating Temperature min.                              | <b>-60 °C</b>         |
| Fuse   | <b>G/5x20</b>         |
| Fuse Type  | <b>Glass</b>          |

## ELECTRICAL FEATURES

|                         |              |
|-------------------------|--------------|
| Nominal Impulse Voltage | <b>6 Kv</b>  |
| Nominal Current         | <b>10 A</b>  |
| Nominal Voltage         | <b>500 V</b> |
| Maximum Load Current    | <b>10 A</b>  |

## CONNECTION DATA

|  |                            |
|--|----------------------------|
| Connection Type  | <b>Spring Connection</b>   |
| Single-core min. conductor cross-section   | <b>0,08 mm<sup>2</sup></b> |
| Single-core max. conductor cross-section   | <b>6 mm<sup>2</sup></b>    |
| Conductor Cross Section Awgkcmil Min   | <b>28 AWG</b>              |
| Conductor Cross Section Awgkcmil Max   | <b>10 AWG</b>              |
| Multi-core min. conductor cross-section  | <b>0,14 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section  | <b>4 mm<sup>2</sup></b>    |
| Multi-core min. conductor cross-section with ferrule                               | <b>0,14 mm<sup>2</sup></b> |
| Multi-core max. conductor cross-section with ferrule                               | <b>4 mm<sup>2</sup></b>    |
| Min. Stripping Length  | <b>8 mm</b>                |
| Max. Stripping Length  | <b>10 mm</b>               |
| Internal cylindrical indicator   | <b>A4</b>                  |
| 2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve | <b>1 mm<sup>2</sup></b>    |

## DIMENSIONS

|                 |                |
|-----------------|----------------|
| Width           | <b>6,2 mm</b>  |
| Length          | <b>76,6 mm</b> |
| Height Mr 35X75 | <b>64,8 mm</b> |
| Height MR 35x15 | <b>72,3 mm</b> |