

TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > FUSE TERMINALS

SRD 4SLD 24V AC/DC Beige

Stock Keeping Unit (SKU): 312130*Cage Clamp Type, with orange button, 4 mm² fuse terminal block (24V)*

Commercial Information

Product Sales Code	312130
Package Unit	30 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.018 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Beige
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-3
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1-HL 2-HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C
Fuse	G/5x20

Fuse Type	Glass
-----------	--------------

ELECTRICAL FEATURES

Nominal Impulse Voltage	6 Kv
Nominal Current	10 A
Nominal Voltage	24 V
Maximum Load Current	10 A

CONNECTION DATA

Connection Type	Spring Connection
Single-core min. conductor cross-section	0,08 mm²
Single-core max. conductor cross-section	6 mm²
Conductor Cross Section Awgkcmil Min	28 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,14 mm²
Multi-core max. conductor cross-section	4 mm²
Multi-core min. conductor cross-section with ferrule	0,14 mm²
Multi-core max. conductor cross-section with ferrule	4 mm²
Min. Stripping Length	8 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A4
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve	1 mm²

DIMENSIONS

Width	6,2 mm
Length	76,6 mm
Height Mr 35X75	64,8 mm
Height MR 35x15	72,3 mm