

TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > GROUNDING TERMINALS

SRD 4T Grey

Stock Keeping Unit (SKU): 337170

Cage Clamp Type, 4 mm² grounding terminal block

Commercial Information

Product Sales Code	**337170**
Package Unit	**50 pcs.**
Customs Tariff Number	**853690950000**
Weight Per Unit Including Packaging	**0.0244 kg.**

Technical Information

PRODUCT SPECIFICATIONS	
Number of Connections	**1**
Number of Levels	**1**
Insulation Material	**PA**
UL 94 Flammability Class	**V0**
Impulse Voltage Category	**III**
Insulation Material Group	**I**
Pollution Degree	**3**
Protective Conductor Type	**PE**
Connection According to Standard	**IEC 60947-7-2**
Fire Protection in Railway Vehicles (DIN EN 45545-2 R22/R23/R24/R26)	**HL 1 - HL 2 - HL 3**
Continuous Operating Temperature Max.	**130 °C**
Continuous Operating Temperature Min.	**-60 °C**

ELECTRICAL SPECIFICATIONS

Nominal Impulse Voltage	**8 Kv**
Nominal Voltage	**1000 V**
Maximum Load Current	**57 A**

CONNECTION DATA

Connection Type	**Spring Connection**
Min. Solid Conductor Cross-Sectional Area	**0,2 mm²**
Max. Solid Conductor Cross-Sectional Area	**10 mm²**
Conductor Cross-Section AWG/kcmil Min.	**24 AWG**
Conductor Cross-Section AWG/kcmil Max.	**8 AWG**
Min. Stranded Conductor Cross-Sectional Area	**0,2 mm²**
Max. Stranded Conductor Cross-Sectional Area	**6 mm²**
Min. Stranded Conductor Cross-Sectional Area with Ferrule	**0,25 mm²**
Max. Stranded Conductor Cross-Sectional Area with Ferrule	**6 mm²**
Max. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	**1,5 mm²**
Min. Stripping Length	**10 mm**
Max. Stripping Length	**12 mm**
Internal Cylindrical Indicator	**A5**

DIMENSIONS

Width	**6,2 mm**
Length	**60,10 mm**
Height MR 35x7.5	**38,30 mm**
Height MR 35x15	**45,80 mm**

Certificates

ATEX | CE | ROHS | UKCA | cULus

ATEX

Conductor Cross-section	AWG 8-24
Nominal Current	43
Nominal Voltage	600

Accessories

ZINC COATED



Product Code: 500601

MR 35x7.5 Straight (1m) Zinc Coated Rail



Product Code: 500604

MR 35x7.5 Slotted DIN Rail (2 m), Galvanized



Product Code: 500602

MR 35x7.5 Slotted (1m) Zinc Coated Rail



Product Code: 500603

MR 35x7.5 Straight (2m) Zinc Coated Rail



Product Code: 500606

MR 35x15 Straight (1m) Zinc Coated Rail

ÇINKO KAPLI



Product Code: 500607

MR 35x15 Slotlu (1m) Çinko Kaplı Ray

GALVANIZED



Product Code: 500602E

MR 35x7.5 Slotted (1m) Rail (Galvanized)



Product Code: 500603E

MR 35x7,5 Plain (2m) Rail (Galvanized)



Product Code: 500604E

MR 35x7,5 SLOT (2m) RAIL (GALVANIZED)

SCREWDRIVERS



Product Code: 561160

KT-D 4 (0,8 x Ø4,0)

TEST SOCKETS

Product Code: 493023

TF (Ø 2,3)

TERMINAL THERMAL PRINTER LABELS



Product Code: 812750

D-NS 8x10

END PLATE/COVER

Product Code: 451259

NPP/SRD 6E Grey

SEPARATION PLATE

Product Code: 464189

APP/SRD 6E Grey

PLUG-IN CROSS CONNECTOR



Product Code: 470122

CS 6/2



Product Code: 470123

CS 6/3



Product Code: 470124

CS 6/4



Product Code: 470125

CS 6/5



Product Code: 470129

CS 6/10

END STOP



Product Code: 497009

KD 3/NM Grey

Product Code: 497019

KD 4/NM Grey

Product Code: 497059

KD 7/NM Grey

Product Code: 497069

KD 8/NM Grey

TERMINAL STRIP LABELS

Product Code: 1020100

SLF-P1 W 11,2mm x 15m