



TERMINAL BLOCKS > SPRING CLAMP TYPE TERMINAL BLOCKS > GROUNDING TERMINALS

SRD 6T Yellow-Green

Stock Keeping Unit (SKU): 337210

Cage Clamp Type, 6 mm² grounding terminal block

Commercial Information

Product Sales Code	337210
Package Unit	60 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.02433 kg.

Technical Information

PRODUCT FEATURES	
Number of Connections	2
Color	Yellow/Green
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-2
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Spring Connection
-----------------	--------------------------

Single-core min. conductor cross-section	0,2 mm²
--	---------------------------

Single-core max. conductor cross-section	10 mm²
--	--------------------------

Conductor Cross Section Awgkcmil Min	24 AWG
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	8 AWG
--------------------------------------	--------------

Multi-core min. conductor cross-section	0,2 mm²
---	---------------------------

Multi-core max. conductor cross-section	6 mm²
---	-------------------------

Multi-core min. conductor cross-section with ferrule	0,25 mm²
--	----------------------------

Multi-core max. conductor cross-section with ferrule	6 mm²
--	-------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	1,5 mm²
--	---------------------------

Min. Stripping Length	10 mm
-----------------------	--------------

Max. Stripping Length	12 mm
-----------------------	--------------

Internal cylindrical indicator	A5
--------------------------------	-----------

DIMENSIONS

Width	8,00 mm
-------	----------------

Length	72,50 mm
--------	-----------------

Height Mr 35X75	44,10 mm
-----------------	-----------------

Height MR 35x15	51,60 mm
-----------------	-----------------