



TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > TRANSFORMER TERMINAL BLOCKS

TRV 10 Grey

Stock Keeping Unit (SKU): 422039

Screw Type, 10 mm² transformer terminal blocks

Commercial Information

Product Sales Code	422039
Package Unit	25 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.03644 kg.

Technical Information

PRODUCT SPECIFICATIONS	
Number of Connections	4
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V2
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC60998-1 / 61558-1
Continuous Operating Temperature Max.	120 °C
Continuous Operating Temperature Min.	-55 °C

ELECTRICAL SPECIFICATIONS	
Nominal Impulse Voltage	8 Kv

Nominal Current	63 A
Nominal Voltage	750 V
Maximum Load Current	63 A

CONNECTION DATA

Connection Type	Screw Connection
Min. Solid Conductor Cross-Sectional Area	0,5 mm²
Max. Solid Conductor Cross-Sectional Area	16 mm²
Conductor Cross-Section AWG/kcmil Min.	20 AWG
Conductor Cross-Section AWG/kcmil Max.	6 AWG
Min. Stranded Conductor Cross-Sectional Area	0,5 mm²
Max. Stranded Conductor Cross-Sectional Area	16 mm²
Min. Stranded Conductor Cross-Sectional Area with Ferrule	0,5 mm²
Max. Stranded Conductor Cross-Sectional Area with Ferrule	10 mm²
Min. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	0,5 mm²
Max. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	6 mm²
Min. Stripping Length	11 mm
Max. Stripping Length	12 mm
Internal Cylindrical Indicator	B6
Tightening Torque Min.	1,2 Nm
Tightening Torque Max.	1,8 Nm

DIMENSIONS

Width	22 mm
Length	35,80 mm
Height	46,00 mm