

ELECTRONICS PRODUCTS > PROTECTION CONTROL & TIME RELAYS > VOLTAGE MONITORING RELAYS



V1

Stock Keeping Unit (SKU): 270159

Voltage Monitoring Relay

Commercial Information

Product Sales Code	270159
Package Unit	1 pcs.
Customs Tariff Number	853649000029
Weight Per Unit Including Packaging	0.066 kg.

Technical Information

General	
Networks	3Ø with Neutral
Connection Type	Screw terminal
Protection Class	IP20
Weight G	66
Packaging Quantity	1
Case Width Mm	17,5
Mounting Type	--
Operating Frequency	50-60Hz
Supply Frequency	35-70Hz
Control Input Voltage Range	----
Response Time For Monitoring Any Function	Max. 250ms
Emc Emi	+
Output Type	Relay

Current Measurement Input

Power Consumption	<3VA AC
-------------------	-------------------

Power Supply

Voltage	L1-N den 85-320VAC AC
---------	------------------------------

Environmental Conditions

Operating Temperature	-20 / +60 °C
-----------------------	---------------------

Storage Temperature	-40°C +75°C
---------------------	--------------------

Relative Humidity Non Condensing	Maks. 95% (no condensation)
----------------------------------	------------------------------------

Backup Connections

Type	1 C/O (SPDT)
------	---------------------

Max Values Ac No Side	5A/250V; 1250VA
-----------------------	------------------------

Max Values Dc No Side	5A/30VDC
-----------------------	-----------------

Mechanical Operating Life	= 10⁷ operations
---------------------------	------------------------------------

Electrical Operating Life No Side	"5×10⁴(5A@250VAC) 1×10⁴(5A@30VDC)"
-----------------------------------	---

Phase Absence

Fixed Delay Time	500ms
------------------	--------------

Adjustable Voltage Protection

Upper Limit	240 - 300VAC (L-N)
-------------	---------------------------

Lower Limit	150 - 210VAC (L-N)
-------------	---------------------------

Hysteresis	6 VAC
------------	--------------

Delay Time	Off delay çalışma için 0.1sn - 10sn arası
------------	--

Adjustable excessive High Low Voltage Protection

Upper Limit	310VAC (L-N)
-------------	---------------------

Lower Limit	140VAC (L-N)
-------------	---------------------

Hysteresis	6VAC
------------	-------------

Delay Time	100ms
------------	--------------

Ptc Protection

Fixed Delay Time	--
------------------	-----------

Threshold

--
