


TERMINAL BLOCKS > OTHER PRODUCTS > SOCKET



VFS 4 Grey

Stock Keeping Unit (SKU): 314019

Screw and Quick Connect Type, 4 mm² transformer terminal blocks

Commercial Information

Product Sales Code	314019
Package Unit	80 pcs.
Customs Tariff Number	853690950000
Weight Per Unit Including Packaging	0.01075 kg.

Technical Information

PRODUCT FEATURES

Number of Connections	6
Color	Grey
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Connection According to Standard	IEC 60947-7-1
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
Nominal Current	32 A
Nominal Voltage	800 V
Maximum Load Current	40 A

CONNECTION DATA

Connection Type	Vidali/Faston baglanti
Single-core min. conductor cross-section	0,2 mm²
Single-core max. conductor cross-section	6 mm²
Conductor Cross Section Awgkcmil Min	24 AWG
Conductor Cross Section Awgkcmil Max	10 AWG
Multi-core min. conductor cross-section	0,2 mm²
Multi-core max. conductor cross-section	6 mm²
Multi-core min. conductor cross-section with ferrule	0,25 mm²
Multi-core max. conductor cross-section with ferrule	4 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Max	2,5 mm²
Min. Stripping Length	9 mm
Max. Stripping Length	10 mm
Internal cylindrical indicator	A4
Tightening Torque Min	0,5 Nm
Tightening Torque Max	0,8 Nm

DIMENSIONS

Width	6,20 mm
Length	54,20 mm
Height Mr 35X75	51,50 mm
Height MR 35x15	59,00 mm
Height Mr 32	55,80 mm