



VT3-AC-24

Stock Keeping Unit (SKU): 600103

True RMS Voltage Transducer

Commercial Information

Product Sales Code	600103
Package Unit	1 pcs.
Customs Tariff Number	854370900019
Weight Per Unit Including Packaging	0.076 kg.

Technical Information

General	
Connection Type	Screw terminal
Protection Class	IP20
Weight G	76
Packaging Quantity	1
Case Width Mm	36
Mounting Type	Panel or Rail
Isolation	1.5 kVrms, 3-way
Response Time	350ms
Linearity	<0.2%
Ripple	<80mV
Accuracy	<0.2% (full scale, 25°C)
Temperature Coefficient	150 ppm/°C
Test Voltage Between Input Output	4 kV during 1 min.

Current Measurement Input

Power Consumption	<1.5W DC / <4VA AC
-------------------	---------------------------------

Power Supply

Voltage	10-36V DC
---------	------------------

Frequency	--
-----------	-----------

Environmental Conditions

Operating Temperature	-20°C +60°C
-----------------------	--------------------

Storage Temperature	-40°C +75°C
---------------------	--------------------

Relative Humidity Non Condensing	Max. 95%
----------------------------------	-----------------

Emc Emi

Radiated Emission Test 61000 6 2Ac	2012, 61000-6-4
------------------------------------	------------------------

Input Signal

Frequency	40-70 Hz
-----------	-----------------

Instantaneous Overload	<2xU Input Max. Range (5 pulses 1 sec.)
------------------------	---

Continuous Overload	Max. 600V
---------------------	------------------

Input Impedance	240 Ohm
-----------------	----------------

Input Signal Adjustable Voltage Range

0 24Vac	+
---------	----------

0 36Vac	+
---------	----------

0 54Vac	+
---------	----------

0 80Vac	+
---------	----------

0 120Vac	+
----------	----------

0 170Vac	+
----------	----------

0 250Vac	+
----------	----------

0 400Vac	+
----------	----------

0 450Vac	+
----------	----------

0 500Vac	+
----------	----------

0 24Vdc	--
---------	-----------

0 54Vdc	--
0 120Vdc	--
0 250Vdc	--
0 450Vdc	--

Input Signal Adjustable Current Range

0 1Aac	---
0 2Aac	--
0 3Aac	--
0 4Aac	--
0 5Aac	--

Output Type

0 20Ma	+
4 20Ma	+
20Ma	+
20 0Ma	+
20 4Ma	+
0 5V	+
10V	+
10 0V	+

Analog Output

Max Current	24 mA
Max Voltage	12V
Max Load	10 0 (for voltage) / 600 Ohm (for current)