


TERMINAL BLOCKS > SCREW TYPE TERMINAL BLOCKS > TEST AND DISCONNECT TERMINALS

WGO 3 Single Test Socket Grey

Stock Keeping Unit (SKU): 375693

6mm² Screw/Spring-Loaded Test and Disconnect Terminal Block (One test socket)

Commercial Information

Product Sales Code	**375693**
Package Unit	**50 pcs.**
Customs Tariff Number	**853690950000**
Weight Per Unit Including Packaging	**0.0348 kg.**

Technical Information

PRODUCT SPECIFICATIONS	
Number of Connections	**2**
Color	**Grey**
Number of Levels	**1**
Insulation Material	**PA**
UL 94 Flammability Class	**V2**
Impulse Voltage Category	**III**
Insulation Material Group	**I**
Pollution Degree	**3**
Connection According to Standard	**IEC 60947-7-1**
Continuous Operating Temperature Max.	**120 °C**
Continuous Operating Temperature Min.	**-55 °C**

ELECTRICAL SPECIFICATIONS	
Nominal Impulse Voltage	**6 Kv**

Nominal Current	**41 A**
Nominal Voltage	**400 V**
Maximum Load Current	**57 A**

CONNECTION DATA

Connection Type	**Screw Connection**
Min. Solid Conductor Cross-Sectional Area	**0,2 mm²**
Max. Solid Conductor Cross-Sectional Area	**10 mm²**
Conductor Cross-Section AWG/kcmil Min.	**24 AWG**
Conductor Cross-Section AWG/kcmil Max.	**8 AWG**
Min. Stranded Conductor Cross-Sectional Area	**0,2 mm²**
Max. Stranded Conductor Cross-Sectional Area	**10 mm²**
Min. Stranded Conductor Cross-Sectional Area with Ferrule	**0,25 mm²**
Max. Stranded Conductor Cross-Sectional Area with Ferrule	**6 mm²**
Min. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	**0,5 mm²**
Max. for 2 Stranded Conductors of the Same Cross-Section with Plastic-Collared Twin Ferrule	**4 mm²**
Min. Stripping Length	**10 mm**
Max. Stripping Length	**12 mm**
Internal Cylindrical Indicator	**B5**
Tightening Torque Min.	**0,8 Nm**
Tightening Torque Max.	**1,2 Nm**

DIMENSIONS

Width	**8 mm**
Length	**70,00 mm**
Height MR 35x7.5	**59,5 mm**
Height MR 35x15	**67 mm**
Height MR 32	**64,1 mm**

Certificates

cULus | CE | EAC | ROHS | UKRAYNA

UKCA | ATEX | TSE

cULus	
Conductor Cross-section	AWG 20-8
Nominal Current	50 A
Nominal Voltage	300 V

CE	
Nominal Current	41 A
Nominal Voltage	250 V

Accessories

END STOP



Product Code: 495049

KD 3 Grey



Product Code: 495059

KD 4 Grey



Product Code: 495219

KD 7 Grey



Product Code: 495229

KD 8 Grey

ZINC COATED



Product Code: 500601

MR 35x7.5 Straight (1m) Zinc Coated Rail



Product Code: 500604

MR 35x7.5 Slotted DIN Rail (2 m), Galvanized



Product Code: 500609

MR 35x15 Slotted (2m) Zinc Coated Rail



Product Code: 500602

MR 35x7.5 Slotted (1m) Zinc Coated Rail



Product Code: 500603

MR 35x7.5 Straight (2m) Zinc Coated Rail



Product Code: 500606

MR 35x15 Straight (1m) Zinc Coated Rail



Product Code: 500608

MR 35x15 Straight (2m) Zinc Coated Rail

ÇINKO KAPLI



Product Code: 500607

MR 35x15 Slotlu (1m) Çinko Kaplı Ray

GALVANIZED



Product Code: 500602E

MR 35x7.5 Slotted (1m) Rail (Galvanized)



Product Code: 500603E

MR 35x7,5 Plain (2m) Rail (Galvanized)



Product Code: 500604E

MR 35x7,5 SLOT (2m) RAIL (GALVANIZED)



Product Code: 500609E

MR 35x15 Slotted (2m) Rail (Galvanized)

SCREWDRIVERS



Product Code: 561240

IKT-D 4 (0,8 x Ø4,0)

TEST SOCKETS



Product Code: 493050

TF (Ø 4)



Product Code: 490100

TSK 10 (Ø4) Orange

Product Code: 490101

TSK 10 (Ø4) Blue

Product Code: 490102

TSK 10 (Ø4) Green

Product Code: 490103

TSK 10 (Ø4) Yellow

Product Code: 49010A

TSK 10 (Ø4) Purple

TERMINAL THERMAL PRINTER LABELS



Product Code: 812750

D-NS 8x10

END PLATE/COVER



Product Code: 450229

NPP/WGO 3 Grey

PLUG-IN CROSS CONNECTOR



Product Code: 476302

IZUK 6/2



Product Code: 476303

IZUK 6/3



Product Code: 476304

IZUK 6/4



Product Code: 476306

IZUK 6/6



Product Code: 476309

IZUK 6/10