

## Z1K-M10A

**Stock Keeping Unit (SKU):** 216024

*Timer Relay*



### Commercial Information

Product Sales Code	<b>216024</b>
Package Unit	<b>1 pcs.</b>
Customs Tariff Number	<b>853649000029</b>
Weight Per Unit Including Packaging	<b>0.08 kg.</b>

### Technical Information

General	
Connection Type	<b>Screw terminal</b>
Protection Class	<b>IP20</b>
Weight G	<b>80</b>
Case Width Mm	<b>18</b>
Mounting Type	<b>Panel &amp; Rail</b>
Supply Frequency	<b>45-65 Hz</b>
Output Type	<b>Relay</b>
Functions	<b>ND, FD, FDF, yMN, yMF, yIR, yNF, yP, yIF, yN</b>
Restore Time	<b>Maks. 100ms</b>
Trigger Input Voltage	<b>12-240V AC/DC</b>

### Power Supply

Voltage	<b>12V DC / 12V AC &amp; 180-265V AC</b>
Power Consumption	<b>&lt;1.5W DC / &lt;5VA AC</b>

### Environmental Conditions

Operating Temperature	<b>-20 to + 60°C</b>
Storage Temperature	<b>-40°C +75°C</b>
Relative Humidity Non Condensing	<b>Max. 95%</b>

### Backup Connections

Type	<b>1 C/O (SPDT)</b>
Max Values Ac No Side	<b>10A/250V; 1250VA</b>
Max Values Dc No Side	<b>5A/30VDC; 150W</b>
Mechanical Operating Life	<b>= 10<sup>7</sup> operations</b>
Electrical Operating Life No Side	<b>5x10<sup>4</sup> (5A@250VAC) 1x10<sup>5</sup> (5A@30VDC)</b>

### Time Interval

Timing 1	<b>0,1 sn .. 10 gün</b>
Timing 2	