

Z1T-SD-500

Stock Keeping Unit (SKU): 216022

Timer Relay



Commercial Information

| | |
|-------------------------------------|---------------------|
| Product Sales Code | 216022 |
| Package Unit | 1 pcs. |
| Customs Tariff Number | 853649000029 |
| Weight Per Unit Including Packaging | 0.8 kg. |

Technical Information

| General | |
|-----------------------|-------------------------|
| Connection Type | Screw terminal |
| Protection Class | IP20 |
| Weight G | 80 |
| Case Width Mm | 18 |
| Mounting Type | Panel & Rail |
| Supply Frequency | 45-65 Hz |
| Output Type | Relay |
| Functions | SD |
| Restore Time | Maks. 100ms |
| Trigger Input Voltage | ---- |

Power Supply

| | |
|-------------------|--------------------------------|
| Voltage | 12-240 VDC / 12-240 VAC |
| Power Consumption | 150-500 VAC AC |

Environmental Conditions

| | |
|----------------------------------|----------------------|
| Operating Temperature | -20 to + 60°C |
| Storage Temperature | -40°C +75°C |
| Relative Humidity Non Condensing | Max. 95% |

Backup Connections

| | |
|-----------------------------------|---|
| Type | 2 NO (SPST) |
| Max Values Ac No Side | 16A/250V; 2000VA |
| Max Values Dc No Side | 5A/30VDC; 150W |
| Mechanical Operating Life | = 10⁷ operations |
| Electrical Operating Life No Side | 5x10⁴ (5A@250VAC) 1x10⁵ (5A@30VDC) |

Time Interval

| | |
|----------|--------------------------|
| Timing 1 | 0,1 sn .. 30 sn |
| Timing 2 | 20 msn .. 500 msn |