



КЛЕММНЫЕ БЛОКИ > ПРУЖИННЫЕ КЛЕММНЫЕ БЛОКИ > ЗАЗЕМЛЯЮЩИЕ КЛЕММЫ

SRD 1,5T Желто-зеленый

Артикул (SKU): 337080

1,5 мм² клемма Cage Clamp проходная

Коммерческая информация

Код продажи продукта	337080
Единица Упаковки	50 шт.
Номер таможенного тарифа	853690950000
Вес за единицу, включая упаковку	0.0093 kg.

Техническая информация

PRODUCT FEATURES	
Number of Connections	2
Color	Yellow/Green
Number of Levels	1
Insulation Material	PA
UL 94 Flammability Class	V0
Impulse Voltage Category	III
Insulation Material Group	I
Pollution Degree	3
Protective Conductor Type	PE
Connection According to Standard	IEC 60947-7-2
Fire Protection In Railway Vehicles Din En 45545 2 R22 R23 R24 R26	HL 1 - HL 2 - HL 3
Continuous Operating Temperature max.	130 °C
Continuous Operating Temperature min.	-60 °C

ELECTRICAL FEATURES

Nominal Impulse Voltage	8 Kv
-------------------------	-------------

CONNECTION DATA

Connection Type	Spring Connection
-----------------	--------------------------

Single-core min. conductor cross-section	0,08 mm²
--	----------------------------

Single-core max. conductor cross-section	1,5 mm²
--	---------------------------

Conductor Cross Section Awgkcmil Min	28 AWG
--------------------------------------	---------------

Conductor Cross Section Awgkcmil Max	16 AWG
--------------------------------------	---------------

Multi-core min. conductor cross-section	0,08 mm²
---	----------------------------

Multi-core max. conductor cross-section	1,5 mm²
---	---------------------------

Multi-core min. conductor cross-section with ferrule	0,14 mm²
--	----------------------------

Multi-core max. conductor cross-section with ferrule	1,5 mm²
--	---------------------------

2 Conductors Of The Same Cross Section Multi Core Twin Ferrule With Plastic Sleeve Min	0,5 mm²
--	---------------------------

Min. Stripping Length	8 mm
-----------------------	-------------

Max. Stripping Length	10 mm
-----------------------	--------------

Internal cylindrical indicator	A1
--------------------------------	-----------

DIMENSIONS

Width	4,2 mm
-------	---------------

Length	52,2 mm
--------	----------------

Height Mr 35X75	37,30 mm
-----------------	-----------------

Height MR 35x15	44,80 mm
-----------------	-----------------