

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ > СИГНАЛЬНЫЕ ПАНЕЛИ (АННУНЦИАТОРЫ)



ANC-8(48VAC/DC)

Артикул (SKU): 604621

Цифровой индикатор тревоги

Коммерческая информация

Код продажи продукта	604621
Единица Упаковки	1 шт.
Номер таможенного тарифа	853180709000
Вес за единицу, включая упаковку	280g kg.

Техническая информация

General	
Connection Type	Screw terminal
Time Interval	0,2,5,10,15,20,25,30 adjustable
Integrated Buttons	4 (Horn, Ack, Delete, Test)
Siren	+
Real Time Data Recording	6080 logs
Battery Life	> 5 years
Protection Class	IP50 (front)IP20 (back)
Weight G	280
Packaging Quantity	1
Diagrams	---
DIMENSIONS	---
Power Supply	
Voltage	110-300V AC/DC ±10%

Frequency	45-65Hz
-----------	----------------

Environmental Conditions

Operating Temperature	-20°C +60°C
Storage Temperature	-30°C +80°C
Relative Humidity Non Condensing	Max. 95%

Communication

Protocol	Modbus RTU
Baud Rate	1200-57600
Parity	
Stop Bit	
Slave Id	
Isolation	2500Vrms

Input Signal

Voltage	24V AC / DC
Frequency	45-65Hz
Quantity	2
Response Time	25±10ms

Output Connections

Output Type	Relay
Number of Connections	8
Type	1 NO (SPST)
Max Values Ac	5A/277V;1385VA
Max Values Dc	5A/30VDC;150W
Mechanical Operating Life	=10⁸ operation
Electrical Operating Life No Side	1x10⁵(5A@250VAC)

Window

Quantity	8
Color	Red / Green selectable

Size Mm	30.5 x 21.6
Illumination	With 4 pcs. red leds or 4 pcs. green led
Fast Flashing	180 Flash / Min
Slow Flashing	60 Flash / Min.
Marking	Laser printed onto standart tracing paper, using templates provided bu Klemsan Inc.

DIMENSIONS

Frontoverall Dimensions Height Mm	96,8
Frontoverall Dimensions Width Mm	96,8
Panel Cutout Dimensions Height Mm	89,6
Panel Cutout Dimensions Width Mm	89,6
Panel Cutout Dimensions Depth Mm	65