

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > КОММУНИКАЦИОННЫЕ ИНТЕРФЕЙСЫ > ШЛЮЗ



ETOR-2

Артикул (SKU): 601401

Ethernet-шлюз (TCP/IP — RS232)

Коммерческая информация

Код продажи продукта	601401
Единица Упаковки	1 шт.
Вес за единицу, включая упаковку	58 kg.

Техническая информация

CONNECTION DATA

Connection Type	Screw Terminal (for supply and serial interface)
-----------------	---

General

Case Width Mm	17,5
Operating Mode	Server or Client Selectable (bidirectional)
Configuration	Mini USB Port or Web Interface
Dhcp Automatic Ip Acquisition	+
Arp	+
Ping Blocking	+
Led Indicators	+
Reset Function	+
Esd Protection	+
Supported Drivers	Microsoft .NET Framework 3.5 üzeri windows işletim sistemleri

Power Supply

Frequency	45-65Hz
-----------	----------------

Mechanical Properties

Weight G	58
Protection Class	IP20
Mounting Type	Rail Mount
Packaging Quantity	1

Environmental Conditions

Operating Temperature	-10°C +60°C
Storage Temperature	-30°C +80°C
Relative Humidity Non Condensing	Max. 95%

Galvanic Isolation

Power Supply Ethernet Port	1500VRMS, 2250VDC
Power Supply Serial Port	1500VRMS, 2250VDC
Serial Port Ethernet Port	2500VRMS

Ethernet Interface

Number Of Ports	1
Operating Modes	Modbus TCP, Modbus RTU over TCP, Modbus ASCII over TCP
Server Mode	6
Receiver Mode	1
Connector	RJ45
Data Transfer Rate	10/100 Base-TX

Serial Interface

Number Of Ports	1
Operating Modes	Modbus RTU, Modbus ASCII
Serial Connection Standard	RS485
Server Mode	1
Receiver Mode	1
Baud Rate	300 to 115200 bps
Data Bits	8

Stop Bits	1 or 2
Parity	None, Even, Odd
