

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > КОММУНИКАЦИОННЫЕ ИНТЕРФЕЙСЫ > ШЛЮЗ



WTOR-4

Артикул (SKU): 601450

WI-FI шлюз

Коммерческая информация

Код продажи продукта	601450
Единица Упаковки	1 шт.

Техническая информация

CONNECTION DATA

Connection Type	Screw terminal
-----------------	-----------------------

General

Case Width Mm	17,5
Configuration	Web Interface
Dhcp Automatic Ip Acquisition	+
Ping Blocking	+
Led Indicators	+
Reset Function	+
Esd Protection	+
Supported Drivers	Microsoft .NET Framework 3.5 üzeri windows isletim sistemleri
Supported Protocols	MODBUS TCP; MODBUS RTU over TCP; MODBUS ACII over TCP
Isolation	1.5kV RMS

Power Supply

Voltage	11-30VDC
---------	-----------------

Frequency	45-65Hz
Consumption	1.2W DC

Mechanical Properties

Weight G	
Protection Class	IP20
Mounting Type	Rail Mount
Packaging Quantity	1

Environmental Conditions

Operating Temperature	
Storage Temperature	
Relative Humidity Non Condensing	%95 non-condensing

Serial Interface

Number Of Ports	1
Serial Connection Standard	RS485
Server Mode	7
Receiver Mode	(-)
Baud Rate	300 to 115200 bps
Data Bits	8
Stop Bits	1-2
Parity	---, Double, Single

Wifi Interface

Standard	802.11b/g/n
Operating Modes	AP(Access point)/ Station Mod
Number Of Remote Connections Server Mode	64
Number Of Remote Connections Receiver Mode	(-)
Security Type	WPA2