

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > КОММУНИКАЦИОННЫЕ ИНТЕРФЕЙСЫ > ШЛЮЗ



2G & 3G GPRS Gateway

Артикул (SKU): 601445

2G & 3G GPRS шлюз

Коммерческая информация

Код продажи продукта	601445
Единица Упаковки	1 шт.

Техническая информация

CONNECTION DATA

Connection Type	Screw terminal
-----------------	-----------------------

General

Case Width Mm	17,5
Configuration	
Dhcp Automatic Ip Acquisition	
Ping Blocking	
Led Indicators	+
Reset Function	+
Esd Protection	+
Supported Drivers	Microsoft .NET Framework 3.5 üzeri windows isletim sistemleri
Supported Protocols	
Isolation	1.5kV RMS

Power Supply

Voltage	11-30VDC
---------	-----------------

Frequency	45-65Hz
Consumption	11-30V DC

Mechanical Properties

Weight G	
Protection Class	IP20
Mounting Type	Rail Mount
Packaging Quantity	1

Environmental Conditions

Operating Temperature	
Storage Temperature	-30°C..+80°C
Relative Humidity Non Condensing	Max.95% (no condensation)

Serial Interface

Number Of Ports	1
Serial Connection Standard	RS485
Server Mode	64
Receiver Mode	64
Baud Rate	300 to 115200 bps
Data Bits	8
Stop Bits	1-2
Parity	None, even, odd

Gprs Multi Slot Class

Downlink	Class 12 Max. 85.6kbps
Uplink	Class 12 Max. 85.6kbps

Edge Multi Slot Class

Downlink	Class 12 Max. 236.8kbps
Uplink	Class 12 Max. 236.8kbps

Communication

Auxiliary Protocols	MODBUS TCP; MODBUS RTU via TCP; MODBUS ACII via TCP
---------------------	--

Operation Type	Serial Master; Transparent
Logging	7-days record (1 ... 60 min) Totally 100,800 records (1 min resolution)
