

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРЕОБРАЗОВАТЕЛИ > ПАССИВНЫЕ ИЗОЛЯТОРЫ



PISO-DC-2(4-20mA/4-20mA)

Артикул (SKU): 602851

Пассивный изолятор DC сигнала

Коммерческая информация

| | |
|--------------------------|---------------------|
| Код продажи продукта | 602851 |
| Единица Упаковки | 1 шт. |
| Номер таможенного тарифа | 854370900019 |

Техническая информация

| General | |
|------------------------------|-----------------------|
| Connection Type | Screw terminal |
| Protection Class | IP20 |
| Diagrams | |
| DIMENSIONS | |
| Case Width Mm | 17,5 |
| Mounting Type | Panel or Rail |
| Isolation | 1.5 kVrms |
| Measurement Error Full Scale | < 0.1% |
| Response Time | 20 ms |
| Temperature Coefficient | < 50 ppm/K |
| Inputs And Outputs | |
| Number Of Input Channels | 2 |
| Input Signal Type | 0-20mA |
| Input Max Signal | 50mA |

| | |
|---------------------------|------------------------------|
| Number Of Output Channels | 2 |
| Output Signal Type | 0-20mA |
| Output Max Current | 24mA |
| Output Max Voltage | --- |
| Output Ripple | <20mV (Full Scale) |
| Output Load Capacity | = 250 Ohm |

Mechanical Properties

| | |
|--------------------|----------|
| Weight G | |
| Packaging Quantity | 1 |

Environmental Conditions

| | |
|----------------------------------|--------------------|
| Operating Temperature | -20°C +60°C |
| Storage Temperature | -40°C +75°C |
| Relative Humidity Non Condensing | Max. 95% |

Emc Emi

| | |
|------------------------------------|------------------------|
| Radiated Emission Test 61000 6 2Ac | 2012, 61000-6-4 |
|------------------------------------|------------------------|