



ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > РЕЛЕ ЗАЩИТЫ И УПРАВЛЕНИЯ > РЕЛЕ КОНТРОЛЯ НАПРЯЖЕНИЯ

G1D-SA-L

Артикул (SKU): 270141

Реле контроля напряжения

Коммерческая информация

Код продажи продукта	270141
Единица Упаковки	1 шт.
Номер таможенного тарифа	853649000029
Вес за единицу, включая упаковку	0.075 kg.

Техническая информация

General	
Networks	3Ø with Neutral
Connection Type	Screw terminal
Protection Class	IP20
Weight G	75
Packaging Quantity	1
Case Width Mm	17,5
Mounting Type	--
Operating Frequency	50-60Hz
Supply Frequency	50-60Hz
Control Input Voltage Range	----
Response Time For Monitoring Any Function	Max. 500ms
Emc Emi	+
Output Type	Relay

Current Measurement Input

Power Consumption	<4VA AC
-------------------	-------------------

Power Supply

Voltage	190-230VAC ±25% from L1-L3
---------	-----------------------------------

Environmental Conditions

Operating Temperature	-20 / +60 °C
-----------------------	---------------------

Storage Temperature	-40°C +75°C
---------------------	--------------------

Relative Humidity Non Condensing	Maks. 95% (no condensation)
----------------------------------	------------------------------------

Backup Connections

Type	1 C/O (SPDT)
------	---------------------

Max Values Ac No Side	10A/250V; 1250 VA
-----------------------	--------------------------

Max Values Dc No Side	5A/30VDC; 150W
-----------------------	-----------------------

Mechanical Operating Life	= 107 operations
---------------------------	-------------------------

Electrical Operating Life No Side	5×10⁴ (5A@250VAC) 1×10⁵ (5A@30VDC)
-----------------------------------	---

Phase Absence

Fixed Delay Time	500ms
------------------	--------------

Phase Sequence

Fixed Delay Time	500ms
------------------	--------------

Adjustablefixed Unbalance Protection

Rangelimit	± (5% => 20%)/ OFF
------------	------------------------------

Hysteresis	3% x Un ~ 6,9VAC
------------	-------------------------

Delay Time	0.1=>10s
------------	--------------------

Adjustable Voltage Protection

Upper Limit	+ (5% => 20%)/OFF
-------------	-----------------------------

Lower Limit	-(5% => 20%)/OFF
-------------	----------------------------

Hysteresis	6 VAC
------------	--------------

Delay Time	0.1=>10s for off delay operation
------------	--

Adjustable Current Protection

Upper Limit	--
Lower Limit	--
Hysteresis	--
Delay Time	--

Adjustable Frequency Protection

Upper Limit	--
Lower Limit	---
Hysteresis	--
Delay Time	--

Adjustable excessive High Low Voltage Protection

Upper Limit	--
Lower Limit	--
Hysteresis	--
Delay Time	--

Ptc Protection

Fixed Delay Time	--
Threshold	--