

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > РЕЛЕ ЗАЩИТЫ И УПРАВЛЕНИЯ > РЕЛЕ ВРЕМЕНИ

Z1K-M2A

Артикул (SKU): 216016

Реле времени



Коммерческая информация

Код продажи продукта	216016
Единица Упаковки	1 шт.
Номер таможенного тарифа	853649000029
Вес за единицу, включая упаковку	0.8 kg.

Техническая информация

General	
Connection Type	Screw terminal
Protection Class	IP20
Weight G	80
Case Width Mm	18
Mounting Type	Panel & Rail
Supply Frequency	45-65 Hz
Output Type	Relay
Functions	yND, yFD
Restore Time	Maks. 100ms
Trigger Input Voltage	----

Power Supply

Voltage	12-240 VDC / 12-240 VAC
Power Consumption	<1,5W DC / <5VA AC

Environmental Conditions

Operating Temperature	-20 to + 60°C
Storage Temperature	-40°C +75°C
Relative Humidity Non Condensing	Max. 95%

Backup Connections

Type	1 C/O (SPDT)
Max Values Ac No Side	10A/250V; 1250VA
Max Values Dc No Side	5A/30VDC; 150W
Mechanical Operating Life	= 10⁷ operations
Electrical Operating Life No Side	5x10⁴ (5A@250VAC) 1x10⁵ (5A@30VDC)

Time Interval

Timing 1	0,1 sn .. 99.9 saat
Timing 2	0,1 sn .. 99.9 saat