

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > РЕЛЕ ЗАЩИТЫ И УПРАВЛЕНИЯ > РЕЛЕ ВРЕМЕНИ

Z1K-M10A

Артикул (SKU): 261024

Реле времени



Коммерческая информация

| | |
|----------------------------------|---------------------|
| Код продажи продукта | 261024 |
| Единица Упаковки | 1 шт. |
| Номер таможенного тарифа | 853649000029 |
| Вес за единицу, включая упаковку | 0.08 kg. |

Техническая информация

| General | |
|-----------------------|---|
| Connection Type | Screw terminal |
| Protection Class | IP20 |
| Weight G | 80 |
| Case Width Mm | 18 |
| Mounting Type | Panel & Rail |
| Supply Frequency | 45-65 Hz |
| Output Type | Relay |
| Functions | ND, FD, FDF, yMN, yMF, yIR, yNF, yP, yIF, yN |
| Restore Time | Maks. 100ms |
| Trigger Input Voltage | 12-240V AC/DC |

Power Supply

| | |
|-------------------|--|
| Voltage | 12V DC / 12V AC & 180-265V AC |
| Power Consumption | <1,5W DC / <5VA AC |

Environmental Conditions

| | |
|----------------------------------|----------------------|
| Operating Temperature | -20 to + 60°C |
| Storage Temperature | -40°C +75°C |
| Relative Humidity Non Condensing | Max. 95% |

Backup Connections

| | |
|-----------------------------------|---|
| Type | 1 C/O (SPDT) |
| Max Values Ac No Side | 10A/250V; 1250VA |
| Max Values Dc No Side | 5A/30VDC; 150W |
| Mechanical Operating Life | = 10⁷ operations |
| Electrical Operating Life No Side | 5x10⁴ (5A@250VAC) 1x10⁵ (5A@30VDC) |

Time Interval

| | |
|----------|-------------------------|
| Timing 1 | 0,1 sn .. 10 gün |
| Timing 2 | |