

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > РЕЛЕ ЗАЩИТЫ И УПРАВЛЕНИЯ > РЕЛЕ ЗАЩИТЫ ДВИГАТЕЛЯ

FP1Y-ASF8 230

Артикул (SKU): 270273

Реле защиты двигателя



Коммерческая информация

Код продажи продукта	270273
Единица Упаковки	1 шт.
Номер таможенного тарифа	853649000029
Вес за единицу, включая упаковку	0.08 kg.

Техническая информация

General	
Networks	3Ø without neutral
Connection Type	Screw terminal
Protection Class	IP20
Weight G	80
Packaging Quantity	1
Case Width Mm	18
Mounting Type	Rail Mount
Nominal Voltage	230 V
Emc Emi	ok
Power Supply	
Voltage	85-300V LN ±20% AC

Frequency	50-60Hz
Consumption	<13VA AC

Environmental Conditions

Operating Temperature	-20 to +60°C
Storage Temperature	-40°C +75°C
Relative Humidity Non Condensing	Max. 95% (no condensation)

Backup Connections

Type	1 C/O (SPDT)
Max Values Ac No Side	10A/250V; 1250 VA
Max Values Dc No Side	5A/30VDC; 150W
Mechanical Operating Life	= 10⁷ operations
Electrical Operating Life No Side	5x10⁴ (5A@250VAC) 1x10⁵ (5A@30VDC)

Monitoring Functions

Phase Loss Delay Time	500 ms
Phase Sequence Delay Time	500 ms
Neutral Loss Delay Time	500 ms
Asymmetry Protection Rangelimit	± 40%
Asymmetry Protection Hysteresis	3% x Un
Asymmetry Protection Delay Time	500ms
Voltage Protection Upper Limit	
Voltage Protection Lower Limit	
Voltage Protection Delay Time	
Number Of Props For Liquid Level Monitoring	
Liquid Level Monitoring Sensitivity	
Liquid Level Monitoring Delay Time	
Light Intensity Monitoring Limit	
Light Intensity Monitoring Delay Time	
Frequency Protection Upper Limit	
Frequency Protection Lower Limit	
Frequency Protection Delay Time	

Ptc Protection Short Circuit Threshold

Ptc Protection High Value Threshold

Ptc Protection Delay Time