

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > РЕЛЕ ЗАЩИТЫ И УПРАВЛЕНИЯ > РЕЛЕ КОНТРОЛЯ НАПРЯЖЕНИЯ



V1D-WS 520

Артикул (SKU): 270281

Реле защиты двигателя

Коммерческая информация

Код продажи продукта	270281
Единица Упаковки	1 шт.
Номер таможенного тарифа	853649000029
Вес за единицу, включая упаковку	0.08 kg.

Техническая информация

General	
Networks	3Ø with neutral
Connection Type	Screw terminal
Protection Class	IP20
Weight G	80
Packaging Quantity	1
Case Width Mm	18
Mounting Type	Rail Mount
Nominal Voltage	400 V
Emc Emi	ok
Power Supply	
Voltage	145-520V LL ±20% AC

Frequency	50-60Hz
Consumption	<13VA AC

Environmental Conditions

Operating Temperature	-20 to +60°C
Storage Temperature	-40°C +75°C
Relative Humidity Non Condensing	Max. 95% (no condensation)

Backup Connections

Type	1 C/O (SPDT)
Max Values Ac No Side	10A/250V; 1250 VA
Max Values Dc No Side	5A/30VDC; 150W
Mechanical Operating Life	= 10⁷ operations
Electrical Operating Life No Side	5x10⁴ (5A@250VAC) 1x10⁵ (5A@30VDC)

Monitoring Functions

Phase Loss Delay Time	500 ms
Phase Sequence Delay Time	500 ms
Neutral Loss Delay Time	ms
Asymmetry Protection Rangelimit	
Asymmetry Protection Hysteresis	
Asymmetry Protection Delay Time	
Voltage Protection Upper Limit	415 - 520 VAC
Voltage Protection Lower Limit	260 - 360 VAC
Voltage Protection Delay Time	"ton= 0.1 .. 10 sn / toff
Number Of Props For Liquid Level Monitoring	
Liquid Level Monitoring Sensitivity	
Liquid Level Monitoring Delay Time	
Light Intensity Monitoring Limit	
Light Intensity Monitoring Delay Time	
Frequency Protection Upper Limit	
Frequency Protection Lower Limit	
Frequency Protection Delay Time	

Ptc Protection Short Circuit Threshold	
Ptc Protection High Value Threshold	
Ptc Protection Delay Time	
Voltage Protection Hysteresis	3% x Un
