

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ > СЧЁТЧИКИ ЭЛЕКТРОЭНЕРГИИ

B45-1M-V1

Артикул (SKU): 606358

1Ø счетчик энергии MID



Коммерческая информация

Код продажи продукта	606358
Единица Упаковки	1 шт.
Номер таможенного тарифа	903032009011
Вес за единицу, включая упаковку	0.08 kg.

Техническая информация

General	
Connection Type	1P2W
Real Time Clock	-
Current Connection Type	Direkt Baglantili (45A ya kadar)
Alarm	
Energy Measurement	
Number Of Tariffs	2
Number Of Sub Tariffs	-
Number Of Reactive Measurement Zones	2
Energy Measurement Type	Import & Export kWh-kVArh
Partial Counter	+
Balance Energy	

Current Measurement Input

Measuring Range	0,25 .. 45A
-----------------	--------------------

Voltage Measurement Input

Measuring Range L N	100-300V AC
---------------------	--------------------

Measuring Range L L	-
---------------------	---

Power Quality Measurements

Harmonic Measurement Current And Voltage	-
------------------------------------------	---

Thdi	-
------	---

Thdv	-
------	---

Power Supply

Voltage	100-300V AC
---------	--------------------

Frequency	45-65Hz
-----------	----------------

Consumption	<3VA AC
-------------	-------------------

Mechanical Properties

Weight G	80
----------	-----------

Protection Class	IP20
------------------	-------------

Mounting Type	Rail Mount
---------------	-------------------

Environmental Conditions

Operating Temperature	-25°C +50°C
-----------------------	--------------------

Storage Temperature	-25°C +70°C
---------------------	--------------------

Relative Humidity Non Condensing	Max. 80% (no condensation)
----------------------------------	-----------------------------------

Communication

Protocol	Modbus RTU
----------	-------------------

Baud Rate	1200-115200
-----------	--------------------

Parity	Odd, Even, None
--------	------------------------

Stop Bit	1
----------	----------

Slave Id	1-247
----------	--------------

Isolation	2750V RMS
-----------	------------------

Digital Output

Frequency	5-30 VDC
Number Of Inputs	2 (1 sabit, 1 ayarlanabilir)
Switched Voltage Range	Transistor
Isolation	3750 Vrms

Digital Input

Number Of Inputs	-
Input Type	-
Isolation	-

Other Measurements

Operating Time Counter	-
Open Time Counter	-
Power Failure Counter	-

Basic Electrical Measurements

Current	-
Voltage	+
Frequency	+
Active Power	+
Reactive Power	+
Apparent Power	+

Cable Cross Sections Power Supply Voltage Relay

multi-core
Single Core

Cable Cross Sections Current

multi-core
Single Core

Cable Cross Sections Digital Inputoutput Rs485 Analog Output

multi-core

Single Core

Measurement Class

En 50470	Class B
----------	----------------

62053 21	-
----------	---

Measurement

Max Min Data	
--------------	--

Demand	+
--------	---

Led Impulse

Kwh	+
-----	---

Kvarh	+
-------	---