

ЭЛЕКТРОННАЯ ПРОДУКЦИЯ > ПРОДУКТЫ УПРАВЛЕНИЯ ЭНЕРГИЕЙ > СЧЁТЧИКИ ЭЛЕКТРОЭНЕРГИИ

## B100-1Q-V2

Артикул (SKU): 606815

3Ø счетчик энергии MID



### Коммерческая информация

Код продажи продукта	<b>606815</b>
Единица Упаковки	<b>1 шт.</b>
Номер таможенного тарифа	<b>903032009011</b>
Вес за единицу, включая упаковку	<b>0.34 kg.</b>

### Техническая информация

General	
Connection Type	<b>3P4W</b>
Real Time Clock	
Current Connection Type	<b>Direkt Baglantili (100A ya kadar)</b>
Alarm	
Energy Measurement	
Number Of Tariffs	<b>1</b>
Number Of Sub Tariffs	
Number Of Reactive Measurement Zones	<b>4</b>
Energy Measurement Type	<b>Import &amp; Export kWh-kVArh</b>
Partial Counter	
Balance Energy	<b>+</b>

## Current Measurement Input

Measuring Range	<b>3x 0,15 .. 100A</b>
-----------------	------------------------

## Voltage Measurement Input

Measuring Range L N	<b>100-300V AC</b>
---------------------	--------------------

Measuring Range L L	<b>173-520</b>
---------------------	----------------

## Power Quality Measurements

Harmonic Measurement Current And Voltage	
--	--

Thdi	<b>+</b>
------	----------

Thdv	<b>+</b>
------	----------

## Power Supply

Voltage	<b>100-300V AC</b>
---------	--------------------

Frequency	<b>45-65Hz</b>
-----------	----------------

Consumption	<b>&lt;3VA AC</b>
-------------	-------------------

## Mechanical Properties

Weight G	<b>340</b>
----------	------------

Protection Class	<b>IP20</b>
------------------	-------------

Mounting Type	<b>Rail Mount</b>
---------------	-------------------

## Environmental Conditions

Operating Temperature	<b>-25°C +50°C</b>
-----------------------	--------------------

Storage Temperature	<b>-25°C +70°C</b>
---------------------	--------------------

Relative Humidity Non Condensing	<b>Max. 80% (no condensation)</b>
----------------------------------	-----------------------------------

## Communication

Protocol	<b>Modbus RTU</b>
----------	-------------------

Baud Rate	<b>1200-57600</b>
-----------	-------------------

Parity	<b>Odd, Even, None</b>
--------	------------------------

Stop Bit	<b>1</b>
----------	----------

Slave Id	<b>1-247</b>
----------	--------------

Isolation	<b>2750V RMS</b>
-----------	------------------

## Digital Output

Frequency

Number Of Inputs

Switched Voltage Range

Isolation

## Digital Input

Number Of Inputs

Input Type

Isolation

## Other Measurements

Operating Time Counter

Open Time Counter

Power Failure Counter

## Basic Electrical Measurements

Current

+

Voltage

+

Frequency

+

Active Power

+

Reactive Power

+

Apparent Power

+

## Cable Cross Sections Power Supply Voltage Relay

multi-core

Single Core

## Cable Cross Sections Current

multi-core

Single Core

## Cable Cross Sections Digital Inputoutput Rs485 Analog Output

multi-core

Single Core

### Measurement Class

En 50470

**Class B**

62053 21

### Measurement

Max Min Data

Demand

**+**

### Led Impulse

Kwh

**+**

Kvarh

**+**